The IMERYS Artoise Clay Tile

Large format interlocking tile with slightly cambered profile

Uniclass

Cl/SfB

L5211

(47) Ng2

- Traditional double roman design
- Low roof pitch suitability (17.5°)
- > variable gauge for ease of fixing
- Excellent high exposure performance

Tiles shown: Burnt Red





Argentique

INNOVATION FOR SUSTAINABLE HOMES

The IMERYS Artoise Clay Tile

Innovative double Roman design



Classic single Roman tiles were introduced into the UK during the 1930s. Imerys Roof Tiles have now produced the Artoise, a new Double Roman Version which still retains the old traditional appeal of this period,offering new build or refurbishment projects a more cost effective option due to its large, more economical size.

Features

The Artoise offers a durable solution in high exposure areas of the UK , due to its double interlocks and comprehensive 30 year durability guarantee.

It comes with a full range of dry fix options for the Ridge, Hip and Verge areas offering a maintenance free solution. Due to its variable 222mm-285mm batten gauge the Artoise has impressive flexibility making the tile quick and easy to install available in six attractive colours.


Colours



Natural Red (076)



Rustic Red (005)



Gloss Black (047)



Burnt Red (034)



Slate (011)



Argentique (015)

To overcome any minor shade variation inherent in the firing of natural materials we recommend that you mix the products on site. The colours shown here are colour reproductions and are shown as a guide. Product samples are available on request.

Technical Data

The Artoise	
Quantity per pallet	240 tiles
Coverage	10 per m² @ 264mm gauge (nominal)
Variable gauge	222-285mm
Overall length	321mm
Overall width	426mm
Working width	389mm
Minimum headlap	73mm
Unit weight	2.6kg
Weight per m²	≈43kg
Minimum roof pitch	17.5°
Batten coverage m ²	3.78 l/m @264mm gauge
Batten sizes	38 x 25mm rafter centres 450mm
	50 x 25mm rafter centres 600mm
Nail size	50 x 3.35mm



Artoise Accessories and Fittings

An extensive range of accessories covering all roofing needs



All Artoise tiles are compatible with IMERYS integrated PV systems





IMERYS Environmental Statement

Our commitment to sustainable development



IMERYS has a corporate policy for sustainable development, making environmental and social implementation a key component of the group's performance. Strict standards are in place for its manufacturing units in terms of emission, water and waste management.

IMERYS ensure responsible environmental management of our quarries, restoration of the landscape, creating valuable wildlife habitats, thus increasing the ecological value, as well as recreation of heathland areas including forestry, replanting with the regeneration of farm land and new leisure areas. IMERYS intends to help improve living conditions in its activities; neighbouring communities working directly with local populations, site managers take action in line with local needs and in partnership with authorities and organisations.

When you select products from the IMERYS range, you can be sure that they have excellent environmental credentials and can achieve an A+ rating in the Building Research Establishment's (BRE) Green Guide to Specification and BS 6001 Responsible Sourcing. This combination with our BS EN 14001 Environmental Management Systems ensure IMERYS products achieve a low carbon footprint to meet the requirements of Code 4 and beyond of the Code for Sustainable Homes.

30 Year Guarantee

IMERYS Roof Tiles are covered by a comprehensive 30 year guarantee of durability provided that they have been installed in compliance with B5534: 2003, BS6399 Part 2:1997 and BS8000-6: 2013 Workmanship on Building Sites. All tiles should be selected from three palettes to ensure a good colour mix. The fixing of roof tiles should comply with wind loads appropriate to the site location and roof design.







* IMERYS roof tiles have excellent environmental credentials and can achieve an A+ Rating in the Building Research Establishment's (BRE) Green Guide to Specification

National Building Specification Clauses (NBS)

All essential clauses for IMERYS roof specifications are available, detailing all work items in section H65 'Single lap roof tiling' and H60 'Plain roof tiling'. Imerys provide detailed fixing advice for the nailing and clipping of all our roof tiles on submission of your project drawings, including site plan and roof elevations in Dwg or PDF format.



NSSPlus

Imerys Roof Tiles Toekomststraat 18, B-9800 Deinze, Belgium Tel: 0161 928 4572 Fax: 0161 929 8513 Email: enquiries.rooftiles@imerys.com